



# BMV INOX



Vertical tank with hollow space (tank in tank system), for a rapid sanitary heating and with antilegionella function, working with hot heating water. Hot sanitary water storage in pressure in stainless steel AISI 316 inspectionable and heat exchanger in good quality steel. Entirely insulated with very high efficiency rigid polyurethane and external finishing in grey PVC. Complete of thermometer and thermostat. maximum storage temperature 99°C

Product CE approved according to P.E.D. norm 97/23/CE, paragraph 3.3.

stainless steel boilers

Model	Capacity liters	Dimensions mm		Weight kg	Sanitary working pressure bar	Primary working pressur bar	heat exchanger power with storage 45 °C and primary 80 °C kW	Hot sanitary water produc- tion da +15°C a +45°C thermo water t.m. +80°C liters		Code
		Ø	H					first 12 min.	first hour	
<b>BMV 200 *</b>	186	560	1125	70	6	4	51,63	512	1600	642940200
<b>BMV 350</b>	355	650	1490	115	6	5	95,58	925	3050	642940350
<b>BMV 500</b>	476	650	1885	145	6	5	130,23	1286	4145	642940500
<b>BMV 800</b>	775	890	1930	290	6	5	168,49	1833	5510	642940800

\* Prearranged with connection for electric resistance

OPTIONAL ACCESSORIES (to be requested when ordering)	
Resistance INCOLOY 825, 2500 W ET - 230/1 V (for mod. 200)	907501036
Thermostat RTS for resistance	907500052