



vers. normal

vers. **MS - MS3V**
(mod. 300)

BSV S1



Vertical tanks double coat vitrified with fix heat exchanger for hot sanitary water production by heat exchange of heating hot water or solar circuit. Entirely insulated with rigid polyurethane (mod. BSV S1 1500 flexible polyurethane demountable), red PVC external finishing. Complete of inspection hatchway. Cathodic protection with magnesium anode/s.

Maximum working pressure: primary 8 bar – secondary 6 bar

Maximum storage temperature: 90°C

Product CE approved according to P.E.D. norm 97/23/CE, paragraph 3.3.

Model	Capacity liters	Dimensions mm		Weight kg	N° solar panels SILE SOLE RT combinable	Heat exchanger power with storage 15+50 °C & primary at tm 70 °C e Δt10 °C kW	Code
		Ø	H				
BSV S1 150 *	150	660	900	60	1	26	502330150
BSV S1 200 *	200	660	1250	70	1	26	502330200
BSV S1 300	300	660	1680	90	2	33	502330300
BSV S1 500	500	710	2040	130	4	50	502330500
BSV S1 750	750	900	1760	147	6	64	502330750
BSV S1 1000	1000	900	2050	178	8	80	502331000
BSV S1 1500	1500	1100	2050	240	12	80	502331500

Package models **M** with MS pump group

BSV S1 300 MS	502340300
----------------------	-----------

* Not available with inspection hatchway

OPTIONAL ACCESSORIES (to be requested when ordering)

Bulb thermometer with sheath	907620037
------------------------------	-----------